

RIDGELINE CONTRACT



PRODUCT SPECIFICATIONS

TYPE	
Construction	Rigid Core Luxury Vinyl + 1mm attached premium pad
Classification	Multi-Layered Flooring
Wear Layer	12mil UV Cured Polyurethane Wear Layer
Edge Profile	4-Sided Micro-Beveled Edges
Size:	7" wide x 48.6" length
Packaging:	30.76 sf/ctn, 55 ctn/plt, 1691.8 sf/plt, 47.5 lbs/ctn
Overall Thickness	4.2 mm

ARCHITECTURAL SPECIFICATION TEST: ASTM F3261, Resilient Rigid Polymeric Core Floor	
ASTM F386/(387): Thickness (With Pad)	Pass
ASTM F410: Wear Layer Thickness	Pass
ASTM F925: Stain/Chemical Resistance	Pass
ASTM F1514: Resistance to Heat Color Change	Pass
ASTM F1515: Resistance to Light Color Change	Pass
ASTM F1914: Residual Indentation	Pass
ASTM 2055: Size & Squareness	Pass
ASTM F2199: Dimensional Stability	Pass
ASTM 2437: Determination of geometrical element	Pass
EN13329: Applicable Standards for floating floors	Meets
ANNEX A&B: Squareness, Height & Opening between Boards	Pass
ASTM D2047: Static COF Polished Surface	Exceeds Industry Standard
ASTM F970-07: Static Load Limit	Pass > 250 Lbs
ASTM E648: Flammability/Radiant Flux	Class 1
Green Certification	GreenGuard Certified

Installation CLICK
TightLock (Angle/Tap) + 1mm Attached Premium Pad

Warranties
25 Year Residential Warranty / 5 Year Light Commercial / 5 Year Multi-Family Warranty

