

ANCHOR

PRODUCT SPECIFICATIONS



Color: Tilbury



Product Specifications

Type

Construction	Layered Luxury Vinyl Consisting of Wear Layer, HD Design Print, 2 Polymeric Cores, Fiberglass Stabilization, and Textured Backing Layer
Wear Layer	Polyurethane Finish
Wear Layer Thickness	20mil
Plank Dimensions & Packaging	5mm x 7.25" x 48" 24.17 sf/ctn, 50 ctn/plt, 1208.5 sf/plt, 47.5 lbs/ctn
Tile Dimensions & Packaging	5mm x 12" x 24" 20 sf/ctn, 60 ctn/plt, 1200 sf/plt, 39 lbs/ctn
Profile	Slight Bevel
Installation	Commercial: Glue Down, Residential: Glue Down or Loose Lay

Recommended Installation Adhesive

Residential & Multi-Family - WF Taylor Dynamic 2098

Commercial - WF Taylor Pinnacle 2091

Warranties

25 Year Residential & Multi-Family

15 Year Commercial

Test Method & Requirements

Flexibility	ASTM F137	Meets
Thickness	ASTM F386	Meets
Wear Layer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Size & Squareness	ASTM 2055	Meets
Dimensional Stability	ASTM F2199	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ATSM E-662	Meets