

DESTINATIONS

PRODUCT SPECIFICATIONS



Product Specifications

Type	
Construction	Layered plank consisting of wear layer, film, core, and backing
Classification	ASTMF 1700, Class III, type B. Solid Vinyl Floor Tile/Plank
Wear Layer	Ceramic Bead
Wear Layer Thickness	12 mil
Size	6" wide x 48" length
Overall Thickness	2.5 mm
Square Feet Per Carton	35.95
Cartons Per Pallet	60
Weight Per Carton	33 lbs

Installation	
Installation Adhesive: Residential & Multi-Family	- WF Taylor Dynamic
Installation Adhesive: Commercial	- WF Taylor Pinnacle

Warranties	
25 Year Residential, 10 Year Light Commercial, 7 Year Commercial	

Test Method & Requirements		
Solid Vinyl Floor Tile	ASTMF1700	Class III, Type B
Flexibility	ASTM F137	Meets
Thickness	ASTM F386	Meets
Wear Layer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM 2055	Meets
Dimensional Stability	ASTM F2199	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Static load limit	ASTM F970, 0.005 in or les	2,000 psi
Smoke Density	ATSM E-662	Meets