

# HARMONY

## PRODUCT SPECIFICATIONS

TYPE	
Construction	Engineered Vinyl Click (EVC) Waterproof Core with Cork Backing
Classification	Multilayered Flooring
Wear Layer	Urethane Ceramic Bead, Textured Finish
Size	6" wide x 48" length
Overall Thickness	7.5mm thick
Wear Layer Thickness	12mil
Pieces Per Carton	10
Cartons Per Pallet	66
Coverage Per Carton	19.48 sq. ft.
Weight Per Carton	32 lbs

TEST	
Resistance to Impact (ASTM F1265-03a)	No Cracking
Abrasion Resistance (ASTM D4060-2010)	32,000 cycles/failure
Castor Chair Resistance (NALFA 3.9)	Class 3, Commercial
Static Load Limit (ASTM F970-07)	0.004", Passes @ 250 psi
Static Coefficient of Friction (ASTM 1028-07)	Pass   0.68 ADA/OSHA requirement
Dimensional Stability (ASTM 2199-09)	Pass   $\leq$ 0.51mm/305mm
Density (ASTM D6111-13a)	> 0.8g/cc
Resistance to Heat (ASTM F1514-03)	Meets < 8.0 Delta E Requirement
Resistance to Light (ASTM F1515-003)	Meets < 8.0 Delta E Requirement
Thickness Swell (ASTM D7519-11)	Class 4, Heavy Commercial
Critical Radiant Flux (ASTM E648-08)	Class 1
Resistance to Chemicals (ASTM F925-13)	Pass
FloorScore Indoor Air Quality	Certified

### INSTALLATION | CLICK

Angle & Tap Lock + 1mm Attached Natural Cork Backing

### WARRANTIES

Lifetime Residential / 5 Year Commercial / 5 Year Multi-Family

