

TANDEM

PRODUCT SPECIFICATIONS



Product Specifications

Type	
Construction	Tandem Engineered Vinyl Click, Waterproof Core w/ Premium Pad
Classification	ASTMF f3261
Wear Layer	Polyurethane
Wear Layer Thickness	20 mil
Size	5.75" wide x 48" length
Overall Thickness	7.5 mm
Square Feet Per Carton	15.30
Cartons Per Pallet	84
Weight Per Carton	21 lbs

Installation

Angle / Angle

Warranties

30 Year Residential, 10 Year Light Commercial

Test Method & Requirements

Resilient Floor in Modular Format w/Rigid Polymeric Core	ASTMF3261	Class III, Type B
Thickness	ASTM F386	Meets
Wear Layer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM 2055	Meets
Dimensional Stability	ASTM F2199	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ATSM E-662	Meets