

TANDEM

LUXURY VINYL | CARPET | HARDWOOD | LAMINATE

Engineered Vinyl Click - 7.5mm Overall, 20mil Wear Layer - Waterproof w/Premium Polymer Core



JBTANDEMACAAWT
Acacia



JBTANDEMASH
Ashford



JBTANDEMDOV
Dover



JBTANDEMGLA
Glasgow



JBTANDEMNR
Norwich



JBTANDEMOBA
Oban



JBTANDEMPREAWT
Preston



JBTANDEMROC
Rockport



JBTANDEMSUS
Sussex



JBTANDEMWIN
Windsor

Dimensions: 7.5mm thick overall x 5-3/4" wide x 48" length

Packaging: 15.3 sf/ctn, 84 ctn/pal, 1285.2 sf/plt

Finish: 20mil Wear Layer, Urethane Finish, Low Gloss

Profile: 4-Sided Micro-Beveled Edges

Installation: Angle/Angle + 2mm Attached Pad

Recommended Cleaner: FreshFloors by WF Taylor

Warranty: 30yr Residential, 10yr Commercial/Multi-Family

Waterproof core with premium waterproof attached pad
4mm thick core and 2mm attached padding will reduce sound transfer
Angle/Angle locking system for easy & fast installation
Low gloss, textured, urethane finish which adds a scratch resistant coating
IIC Rating of 57 (8" slab w/o drop ceiling) | www.acoustics.com/iic.asp



CERTIFIED BY
SCS Global Services

Installation Fast Facts:

- Radiant Heat: Approved (Hydro Systems ONLY)
- Relative Humidity: 30% - 50%
- Acclimation: 24 hrs in carton
- Room Temperature: 70°F
- Expansion Space: 1/4" around perimeter
- Use T-Mold in spaces larger than 26' l x 36' w
- Inspect flooring prior to installation
- Use floor protection for furniture

Read Complete Instructions Before Installing