

# TANDEM RIGID

## PRODUCT SPECIFICATIONS



Color: Coventry

### Product Specifications

#### Type

Construction	Layered plank consisting of wear layer, film, rigid polymeric core, and backing
Classification	ASTM F3261, Resilient floor in modular format with rigid polymeric core
Wear Layer	Polyurethane Finish
Wear Layer Thickness	12mil
Moor Color Size	7.25" wide x 49" length x 4.5mm thick
Other Color Size	7.25" wide x 48" length x 4.5mm thick
Moor Color Packaging	28.95 sf/ctn, 45 ctn/plt, 1303 sf/plt
Other Color Packaging	28.21 sf/ctn, 45 ctn/plt, 1269 sf/plt

#### Installation

Floating, Angle/Angle

#### Warranties

25 Year Residential and Multi-Family, 5 Year Light Commercial

#### Test Method & Requirements

Resilient Floor in Modular Format w/Rigid	ASTM F3261	
Thickness with pad	ASTM F386/387	Meets
Wear Layer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM F2055	Meets
Dimensional Stability w/Exposure to Heat	ASTM F2199	Meets
Dimensional Stability w/Exposure to Heat	ISO 23999	Meets
Determination of Geometrical Character	ISO 24337	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ATSM E662	Meets