

ANCHOR

PRODUCT SPECIFICATIONS



Color: Tilbury

Product Specifications

Type	
Construction	Layered Luxury Vinyl Consisting of Wearlayer, HD Design Print, 2 Polymeric Cores, Fiberglass Stabilization, and Textured Backing Layer
Wearlayer	Polyurethane Coating
Wearlayer Thickness	20mil
Plank Dimensions & Packaging	5mm t x 7.25" w x 48" l 24.17 sf/ctn, 50 ctn/plt, 1208.5 sf/plt
Tile Dimensions & Packaging	5mm t x 12" w x 24" l 20 sf/ctn, 60 ctn/plt, 1200 sf/pl
Profile	4-Sided Micro Bevel
Installation	Commercial: Glue Down, Residential: Glue Down or Loose Lay

Recommended Installation Adhesive	
Residential & Multi-Family	WF Taylor Dynamic 2098
Commercial	WF Taylor Pinnacle 2091

Warranties	
Residential & Multi-Family	20 Yr Residential & Multi-Family
Commercial	15 Yr Commercial

Test Method & Requirements		
Flexibility	ASTM F137	Meets
Thickness	ASTM F386	Meets
Wearlayer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Size & Squareness	ASTM 2055	Meets
Dimensional Stability	ASTM F2199	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ATSM E-662	Meets