

# TANDEM WIDE

## PRODUCT SPECIFICATIONS



### Product Specifications

Type	
Construction	Tandem Wide Engineered Vinyl Click, Waterproof Core w/ Premium Pad
Classification	ASTM F3261
Wear Layer	Polyurethane
Wear Layer Thickness	20mil
Size	7" wide x 48" length
Overall Thickness	7.3mm
Square Feet Per Carton	23.60
Cartons Per Pallet	60
Weight Per Carton	36 lbs

### Installation

Angle /Angle	
--------------	--

### Warranties

30 Year Residential, 10 Year Light Commercial
---

### Test Method & Requirements

Resilient Floor in Modular Format w/Rigid Polymeric Core	ASTM F3261	Class III, Type B
Thickness	ASTM F386	Meets
Wear Layer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM 2055	Meets
Dimensional Stability w/ Exposure to Heat	ASTM F2199	Meets
Dimensional Stability w/ Exposure to Heat	ISO 23999	Meets
Determination of Geometrical Characteristics	ISO 24337	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load Limit	ASTM F970	>250 lbs
Smoke Density	ATSM E-662	Meets