

BOURBON STREET

PRODUCT SPECIFICATIONS

Physical Construction

Construction	Crystal Embossed, Beveled & Waxed Edges w/2mm Attached Pad
Size	5" Wide x 47-13/16" Length
Overall Thickness	8mm
Pieces Per Carton	14
Coverage Per Carton	23.07 sq. ft.
Weight Per Carton	36 lbs
AC Wear Rating	AC3

Environmental

E1 Certified Emissions Rating
CA-CARB Phase 2 Compliant

Testing

Formaldehyde Emission (ASTM D6007)	<0.05 (Class E1), CA-CARB Phase II Compliant
Surface Burning Characteristics (EN ISO 9239-1)	N/A
Reaction to Fire Classification (EN 13501-1)	C1 - S1
Ignitability - Surface Exposure (EN ISO 11925-2)	N/A
Impact Insulation Class IIC (ASTM E492, E989)	7-1/2" slab, no ceiling, IIC 59
Impact Resistance (EN 13329)	≥IC1
Wear Resistance (EN 13329)	AC3 (IP Class 3); ≥ 2,000
Thickness Swell (EN 13329)	≤18%
Determination of overall thickness (EN 13329)	≤18%
Density	≤18%
Scratch Resistance	≥4.0
Sound Testing (6" Concrete Slab with Suspended Ceiling)	STC 63, IIC 67

Warranties

29 Year Residential Warranty

Installation

Installation Method	Drop Lock Locking System
---------------------	--------------------------