

# GIBRALTAR

## PRODUCT SPECIFICATIONS



SCS Certified



### Product Specifications

Type	
Construction	Rigid Core consisting of wearlayer, film, rigid core, and 1mm Pad
Classification	ASTM F3261, Resilient floor in modular format with rigid polymeric core
Finish Coat	Polyurethane
Wearlayer Thickness	20mil
Size	9" width x 60" length
Overall Thickness	6mm
Edge Profile	4-Sided Micro Bevel
Square Feet Per Carton	22.09
Cartons Per Pallet	52
Weight Per Carton	38.25 lbs

### Installation

Method: Angle/Angle

### Warranties

30 Yr Residential, 10 Yr Light Commercial, 10 Yr Multi-Family

### Test Method & Requirements

Resilient Floor in Modular Format w/Rigid Polymeric Core	ASTM F3261	Meets
Thickness	ASTM F386/387	Meets
Wear Layer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM F2055	Meets
Size & Squareness by Dial Guage	ASTM F2421	Meets
Dimensional Stability	ASTM F2199	Meets
Dimensional Stability W/Exposure to Heat	ISO 23999	Meets
Determination of Geometrical Element	ISO 24337	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ASTM E662	Meets

Additional Specifications, Full Installation Instructions & Warranty Information Available at [www.tasflooring.com](http://www.tasflooring.com) | a division of **TAS supply company, inc.**

TASPLVRCF326120.1 | Gibraltar\_MAY 2020\_R1