


# ECLIPSE SOLSTICE

## PRODUCT SPECIFICATIONS



SCS Certified



### Product Specifications

Type	
Construction	Rigid Core vinyl clic consisting of wearlayer, film, waterproof core, and backing
Classification	ASTM F3261, Resilient floor in modular format with rigid polymeric core
Finish Coating	Polyurethane
Wearlayer Thickness	12mil
Size	7" width x 48" length
Overall Thickness	5.0mm
Edge Profile	4-sided Micro Bevel
Square Feet Per Carton	23.09
Cartons Per Pallet	60
Weight Per Carton	37.5 lbs.

Installation	
Method:	Angle/Drop & Tap

Warranties	
Warranty:	25 Yr Residential, 5 Yr Light Commercial, 5 Yr Multi-Family

Test Method & Requirements		
Resilient Floor in Modular Format w/Rigid Polymeric Core	ASTM F3261	Meets
Thickness	ASTM F386/387	Meets
Wear Layer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM F2055	Meets
Dimensional Stability	ASTM F2199	Meets
Dimensional Stability W/Exposure to Heat	ISO 23999	Meets
Determination of Geometrical Element	ISO 24337	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ASTM E662	Meets

Additional Specifications, Full Installation Instructions & Warranty Information Available at [www.tasflooring.com](http://www.tasflooring.com) | a division of **TAS supply company, inc.**