

ECLIPSE

Solstice Series

LUXURY VINYL | CARPET | HARDWOOD | LAMINATE

Waterproof Rigid Core - 5mm Overall, 12mil Wearlayer, w/Pad Attached



WIRC0202
Meteor



WIRC0203
Zenith



WIRC0204
Millenia



WIRC0206
Lyra

SPECIFICATIONS

Dimensions: 7" width x 48" length x 5mm thick overall (4mm core plus 1mm attached pad)

Packaging: 23.09 sf/ctn, 60 ctn/pal, 1385.4 sf/plt

Finish: 12mil Wearlayer, Polyurethane Coating

Profile: 4-Sided Micro-Bevel


Installation: Angle/Drop/Tap

Recommended Cleaner: FreshFloors by WF Taylor

Warranty: 25 Yr Residential, 5 Yr Light Commercial, 5 Yr Multi-Family

BENEFITS

- Waterproof core with attached pad
- Premium attached padding to reduce sound transfer
- Angle/Drop/Tap locking system for easy & fast installation
- Low gloss, textured, high performance polyurethane finish which adds a scratch resistant coating



Installation Fast Facts:

Always Read and follow complete installation instructions.

- Flooring must be allowed to freely float, with proper expansion space.
- Do not install cabinets or other heavy objects over flooring.
- Expansion Space at Vertical Surfaces: Minimum 1/4"
- Maximum Width/Length without T-Mold: 80 linear feet
- Maximum space without T-Mold: 6,400 square feet
- Climate Control: 30-50% Relative Humidity (RH)
- Temperature control prior-during-after Installation: 65-80° F
- Acclimate Flooring: Achieve Normal Room Conditions
- Use floor protection under furniture legs
- Use chair pads under rolling castors
- Radiant Heat : approved (Hydro Systems Only)
- Floor Flatness: Maximum 3/16" in 10 linear feet
- Temperature range after installation: 0-140° F, temperature changes must be gradual, no more than 5 degrees per hour.