

FORTITUDE ABA

PRODUCT SPECIFICATIONS



Product Specifications

| Type | |
|------------------------|---|
| Construction | Rigid Core vinyl click consisting of wearlayer, film, ABA rigid core, and 1mm Pad |
| Classification | ASTM F3261, Resilient floor in modular format with rigid polymeric core |
| Wearlayer | Polyurethane |
| Wearlayer Thickness | 20mil |
| Size | 7.25" width x 48" length |
| Overall Thickness | 5mm |
| Edge Profile | 4-Sided Micro Bevel |
| Square Feet Per Carton | 24.01 |
| Cartons Per Pallet | 60 |
| Weight Per Carton | 42 lbs. |

Installation

Method: Angle/Angle

Warranties

30 Yr Residential, 10 Yr Light Commercial, 10 Yr Multi-Family

Test Method & Requirements

| | | |
|--|---------------|---------------------------|
| Resilient Floor in Modular Format w/Rigid Polymeric Core | ASTM F3261 | Meets |
| Thickness | ASTM F386/387 | Meets |
| Wear Layer Thickness | ASTM F410 | Meets |
| Stain/Chemical Resistance | ASTM F925 | Meets |
| Resistance to Heat | ASTM F1514 | Meets |
| Resistance to Light | ASTM F1515 | Meets |
| Residual Indentation | ASTM F1914 | Meets |
| Size & Squareness | ASTM F2055 | Meets |
| Dimensional Stability | ASTM F2199 | Meets |
| Dimensional Stability W/Exposure to Heat | ISO 23999 | Meets |
| Determination of Geometrical Element | ISO 24337 | Meets |
| Static Coefficient Polished Surface | ASTM D2047 | Exceeds Industry Standard |
| Flammability/Radiant Flux | ASTM E648 | Class I |
| Static Load | ASTM F970 | >250 lbs |
| Smoke Density | ASTM E662 | Meets |

Additional Specifications, Full Installation Instructions & Warranty Information Available at www.tasflooring.com | a division of **TAS supply company, inc.**