

TANDEM WIDE

PRODUCT SPECIFICATIONS



Product Specifications

Type	
Construction	Multi-layer vinyl click consisting of wear layer, direct print film, waterproof expanded polymeric core, LV gauge layer, and backing
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Finish Coat	Polyurethane, Embossed
Wear Layer	20mil thick
Size	7.09" width x 48.03" length (180mm width x 1220mm length)
Overall Thickness	7.5mm (4mm core, 1.5mm LV Gauge, plus 2mm pad)
Edge Profile	4-Sided Micro Bevel
Square Feet Per Carton	28.365sf
Cartons Per Pallet	50
Weight Per Carton	40.75 lbs.

Installation	
Method:	Angle/Angle

Warranties	
30 Yr Residential, 10 Yr Light Commercial, 10 Yr Multi-Family	

Test Method & Requirements		
Resilient Floor in Modular Format w/Rigid Polymeric Core	ASTM F3261	Meets
Thickness	ASTM F386/387	Meets
Wear Layer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM F2055	Meets
Dimensional Stability	ASTM F2199	Meets
Dimensional Stability W/Exposure to Heat	ISO 23999	Meets
Determination of Geometrical Element	ISO 24337	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ASTM E662	Meets