

# LATITUDES 7.5

## PRODUCT SPECIFICATIONS

### Physical Construction

Construction	Engineered Multi-Ply Core, 1/2" Thick Hardwood
Species	European Oak
Texture	Wire Brushed
Wear Layer	2mm Urethane
Gloss Level	Low Gloss
Edge Finish	4-Sided Micro-Beveled Edges
Size	7.5" Wide x (Up to 82" Varied Lengths)
Plank Thickness	.5 inches
Cartons Per Pallet	55
Coverage Per Carton	25.8 sq. ft.
Weight Per Carton	34 lbs

### Testing

HUD/FHA Requirements	Meets
CARB Composite Wood ATCM	CARB Phase II, Certificate # SCS-CARB-000238

### Installation

Installation Method	Tongue & Groove (Nail/Staple/Glue/Float)
Installation Recommended Adhesive	Ironwood or Ridgeline by WF Taylor
Subfloor Requirements	Above, On or Below Grade
Trim and Molding	Color matching pre-finished: reducer strip, stair nosing, end cap, t-molding, wall base and quarter round.

### Warranties

Lifetime Structural Warranty / 25 Year Finish Warranty

### Care & Maintenance

Ordinary sweeping and mopping is usually sufficient to keep the floor clean. If needed, an occasional cleaning with FreshFloors by WF Taylor or equivalent is recommended. Never flood the floor with water. Do not use soap-based detergents, as these may leave a dull finish on the floor. Do not use abrasive cleaners, steel wool, or scouring powder, as these may dull the floor. Dirt, wetness, and improper maintenance may cause significant variation in actual performance. Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance. This product is intended solely for use as an indoor covering and is not recommended or sold for any other purpose. Use entryways systems outside each entrance to prevent dirt, and other substrates from being tracked onto floor.



CA-CARB Phase 2  
Compliant