

# ANCHOR

## PRODUCT SPECIFICATIONS



### Product Specifications

Type		
Construction	Layered Luxury Vinyl consisting of Wearlayer, HD Design Print, 2 Polymeric Cores, Fiberglass Stabilization, and Textured Backing Layer	
Classification	Vinyl Floor Tile/Plank	
Wearlayer	20mil Polyurethane	
Plank Size	7.25" width x 48" length	
Tile Size	12" width x 24" length	
Overall Thickness	5mm	
Plank Packaging	24.17 sf/ctn, 50 ctn/plt	
Tile Packaging	20 sf/ctn, 60 ctn/plt	
Installation		
Glue Down Adhesive: Residential & Multi-Family	WF Taylor Dynamic	
Glue Down Adhesive: Commercial	WF Taylor Pinnacle	
Optional Loose Lay in Residential Applications		
Warranties		
20 Yr Residential, 15 Yr Light Commercial, 15 Yr Multi-Family		
Test Method & Requirements		
Flexibility	ASTM F137	Meets
Thickness	ASTM F386	Meets
Wearlayer Thickness	ASTM F410	Meets
Resistance to Stain/Chemical	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Size & Squareness	ASTM F2055	Meets
Dimensional Stability	ASTM F2199	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ASTM E662	Meets

Additional Specifications, Full Installation Instructions & Warranty Information Available at [www.tasflooring.com](http://www.tasflooring.com) | a division of **TAS supply company, inc.**