

EXPEDITION

PRODUCT SPECIFICATIONS



Product Specifications

Type	
Construction	Layered plank consisting of wearlayer, film, stabilization core, and backing
Classification	ASTM F1700, Class III, Type B - Solid Vinyl Floor Tile/Plank
Wearlayer	Polyurethane
Wearlayer Thickness	12mil
Size	6" width x 48" length
Overall Thickness	2.0mm
Square Feet Per Carton	35.96
Cartons Per Pallet	78
Weight Per Carton	28 lbs

Installation	
Glue Down Adhesive: Residential & Multi-Family	WF Taylor Dynamic
Glue Down Adhesive: Commercial	WF Taylor Pinnacle

Warranties	
20 Yr Residential, 5 Yr Light Commercial/Multi-Family	

Test Method & Requirements		
Solid Vinyl Floor Tile	ASTM F1700	Class III, Type B
Flexibility	ASTM F137	Meets
Thickness	ASTM F386	Meets
Wearlayer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM F2055	Meets
Dimensional Stability	ASTM F2199	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ASTM E662	Meets

Additional Specifications, Full Installation Instructions & Warranty Information Available at www.tasflooring.com | a division of **T&A supply company, inc.**