

RIDGELINE

PRODUCT SPECIFICATIONS



Product Specifications

Type	
Construction	Rigid Core multi-layer vinyl click consisting of wear layer, film, 4mm rigid core, and 1mm Pad
Classification	ASTM F3261, Class I, Type B, Grade 2, Class B
Finish Coat	Polyurethane Coating, Embossed
Wear Layer	12mil
Size	7" width x 48" length / 176mm width x 1212mm length 7" width x 48.5" length / 178mm width x 1235mm length*
Overall Thickness	5mm (4mm core plus 1mm pad)
Edge Profile	4-Sided Micro Bevel
Square Feet Per Carton	25.27/23.66*
Cartons Per Pallet	55
Weight Per Carton	43.5 lbs. /41.5 lbs.*

Installation

Method: Angle/Angle

Warranties

25 Yr Residential, 5 Yr Light Commercial, 5 Yr Multi-Family

Test Method & Requirements

Resilient Floor in Modular Format w/Rigid Polymeric Core	ASTM F3261	Meets
Thickness	ASTM F386/387	Meets
Wear Layer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM F2055	Meets
Dimensional Stability	ASTM F2199	Meets
Dimensional Stability W/Exposure to Heat	ISO 23999	Meets
Determination of Geometrical Element	ISO 24337	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ASTM E662	Meets

Additional Specifications, Full Installation Instructions & Warranty Information Available at www.tasflooring.com | a division of **T&A supply company, Inc.**

TASPLVRCF326120.1 | Ridgeline_JUL 2020_R2