

HARDWOOD | CARPET | LUXURY VINYL | LAMINATE

1/2" thick, European Oak, Thermal Enhanced, Engineered Multi-ply Core



HFTALVRO1275CP
Canoe Point



HFTALVRO1275HV
Haven



HFTALVRO1275ON
Old Northern



HFTALVRO1275SB
Steamboat



HFTALVRO1275TB
Tribunal

SPECIFICATIONS

Dimensions: (Nominal)

1/2" thick x 7.5" wide x multi-length up to 75" length

Packaging: 31 sf/ctn, 45 ctn/plt, 1395 sf/plt

Construction: Sliced veneer over engineered multi-ply core

Finish: Low Gloss, UV Cured Urethane

Texture: Thermal Enhanced, Brushed

Profile: 4-Sided Micro Bevel

Installation: Tongue & Groove (Nail, Staple, Glue, Glue Assist)

Warranty: Limited Lifetime Structural, 30 Yr Residential, 5 Yr Light Commercial

Recommended Adhesive: WF Taylor Ironwood or Ridgeline

Recommended Cleaner: WF Taylor FreshFloors

BENEFITS

- Thermal Enhanced - heating process amplifying dimensional stability
- 70% less susceptible to moisture and humidity changes
- Richer hues and more uniform color throughout
- UV Cured High Performance Aluminum Oxide finish protects floor from wear and damage
- Wide variety of color and grain variation from board-to-board

Additional Specifications, Full Installation Instructions & Warranty Information Available Online www.tasflooring.com | a division of

T&A supply company, Inc.



Installation Fast Facts:

- Radiant Heat: Approved (Hydronic Systems Only)
- Acclimate product to normal room conditions
- Moisture Content: Not to exceed 11%
- Relative Humidity: 35%-55%
- Expansion Space: 3/8" gap
- Recommended Room Temp: 60°F -85°F after install

Read Complete Instructions Before Installing