

3/4" thick, Engineered White Oak, 6mm Sawn Face



Marigold
SOOLYMPUSMA



Polo Fields
SOOLYMPUSPO



Semper Fi
SOOLYMPUSSE

SPECIFICATIONS

Dimensions: (nominal) 3/4" thick x 7.5" wide x 96.5" length
 Construction: Engineered White Oak, 6mm Sawn Face
 Finish: Matte, UV Cured Urethane Coating
 Edge Profile: 4-sided Micro Bevel
 Installation: Tongue & Groove (Float/Glue/Nail)
 Warranty: Residential: Lifetime Structural/25 Year Surface
 Commercial: 5 Year Structural and Surface
 Packaging: 20.042 sf/ctn, 55 ctn/plt, 1108.3 sf/plt
 Recommended Adhesive: WF Taylor Ironwood or Ridge
 Recommended Cleaner: WF Taylor FreshFloors



BENEFITS

- Rich and on-trend colors
- Radiant Heat Approved
- Robust matte lacquer finish with wire brushed texture add a rustic feel to a dynamically wear resistant floor.

Installation Fast Facts:

- Acclimate to normal room conditions
- Moisture Content: 6% - 8%
- Relative Humidity: 30% - 60%
- Temperature after installation: 60° - 85°F
- Expansion Space: 5/8" gap
- Max Room Size: 30' x 50'
- Inspect flooring prior to installation
- Use floor protection for furniture

Read Complete Instructions Before Installing