

CRUISER

2.5 MM, 12 MIL



CTLV0201 | **Yacht**



CTLV0202 | **Clipper**



CTLV0203 | **Catamaran**



CTLV0205 | **Sloop**



CTLV0206 | **Skipjack**



CTLV0207 | **Monitor**

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Classification	ASTM F1700, Class III, Type B
Dimensions	7" Wide x 60" Long, 185 mm x 1524mm
Overall Thickness	2.5 mm
Wear Layer	12 mil
Finish Coat	UV Ceramic Bead
Texture	Embossed
Edge Profile	Soft Rolled
Packaging	54.625 sf/carton - 40 carton/pallet - 2185 sf pallet
Installation	Glue Down
Recommended Adhesive	WF Taylor: Pinnacle, Dynamic or Resolute
Warranty	5 Yr Light Commercial, 5 Yr Multi-Family, 20 Yr Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F, RH Between 35% - 55%
- Do not net or compression fit
- Minimum 3500 PSI for Concrete/Gypsum
- Hydro Radiant Heat approved (≤ 85°F)
- Roll flooring immediately after installation in two directions, reroll 2 hours later
- Follow adhesive instructions for substrate moisture, coverage, PH, porosity, and open time
- Repair or replace worn trowel notches
- Insure floor flatness to within 1/8" in 6'

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE**



SCS Certified

