

## LAMINATE 8 MM + 1.5 MM EVA ATTACHED PAD



**Karsten** | CH50101660002



**Fallen Oak** | CH50101768004



**Shadow Creek** | CH50101810002



**Aldarra** | CH50102043002



**Brighton** | CH5010842011



**Broadmoor** | CH5011193011



**Sandstone** | CH5011270008

### SPECIFICATIONS

Construction	8 mm Water Resistant Standard Core + 1.5 mm EVA Attached Pad
Dimensions	6.5" Wide x 48" Long, 166 mm x 1210 mm
Overall Thickness	9.5 mm (includes 1.5 mm pad)
Wear Surface	AC4
Texture	EIR or Embossed
Edge Profile	4-Sided Painted Bevel
Installation	Angle / Drop & Tap
Warranty	Lifetime Residential, 15 Yr Light Commercial, 15 Yr Multi-Family
Packaging	21.64 sf/carton - 45 carton/pallet - 973.8 sf/pallet

### INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Relative Humidity: 35%-55%
- Recommended Room Temp: 60°F-85°F after install
- Transitions required for rooms larger than 25'L or 35"W
- Subfloors dry and flat (3/16" in 10')
- Installation on or below grade concrete requires 6 mil moisture barrier

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE  
TRIMS, TRANSITIONS & QNOSE**



72 Hour Topical

Additional Specifications, Full Installation Instructions & Warranty Information Available Online

tasflooring.com | a division of **TAS** supply company, Inc.