

Why Ambiance?

The Ambiance collection features a unique ABA construction consisting of two LV "A" layers with a foamed SPC "B" layer. This innovative core creates both a lightweight and dimensionally stable product. Ambiance's lighter construction also allows for more efficient transportation and installation. With an LV top layer, this floor is more compression and indent resistant. Finally, Ambiance's 10 mm overall thickness also provides a more premium experience to the end user.

Specifications

Construction: LSPC Hybrid Luxury Vinyl, ABA Foam Rigid Core Dimensions: 7.125" Wide x 60" Long, 181 mm x 1524 mm

Overall Thickness: 10 mm (includes 2 mm IXPE pad)

Wear Layer: 20 mil

Finish Coat: Low Gloss, Polyurethane

+ Antimicrobial & Anti-Scratch Coating

Texture: Embossed

Edge Profile: 4-Sided Painted Bevel

Installation: Angle / Angle, Float

Packaging: 23.75 sf/ctn - 40 ctn/plt - 950 sf/plt

Warranty: 30 Yr Residential, 10 Yr Light Commercial, 10 Yr Multi-Family

DID YOU KNOW?



THICKER PLANK

Ambiance's 10 mm overall thickness allows for minimal transitions to carpet and tile.



OUIETER UNDERFOOT

Innovative core construction results in a quieter environment and reduces sound transfer.



PEACE OF MIND WATERPROOF

Ambiance's waterproof core protects against spills and splashes, providing peace of mind within the busiest of households.



INNOVATIVE CONSTRUCTION

Ambiance's LSPC, ABA construction combines the LVT top and bottom layers common in WPC flooring with an SPC foamed core resulting in a unique, hybrid experience.



A Division of Supply company, Inc.