AMBIANCE



ABA LSPC 10 MM, 20 MIL

Construction	LSPC Hybrid Luxury Vinyl, ABA Foam Rigid Core
Classification	ASTM F3261, Class 1, Type B, Grade 1, Class B
Dimensions	7.125" Wide x 60" Long, 181 mm x 1524 mm
Overall Thickness	10 mm (Includes 2 mm pad)
Attached Pad	2 mm IXPE Sound Abatement Pad
Wear Layer	20 mil
Finish Coat	Low Gloss, Polyurethane + Antimicrobial & Anti-Scratch Coatings
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	23.75 sf/carton - 40 cartons/pallet - 950 sf/pallet

Installation & Maintenance

Angle / Angle

Expansion & Transition: 1/4" Expansion required at perimeter and at all vertical surfaces. Transition required for rooms larger than 50' W x 50' L.

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit Maintenance: No Polish, Fresh Floors by Taylor

Test Method & Requirements


Resilient Floor in Modular Format	ASTM F3261	Pass
Thickness (with Pad)	ASTM F386/ (387)	Pass
Wear Layer Thickness	ASTM F410	Pass
Stain/Chemical Resistance	ASTM F925	Pass
Resistance to Heat Color Change	ASTM F1514	Pass
Resistance to Light Color Change	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2055	Pass
Dimensional Stability w/Exposure to Heat	ASTM F2199	Pass
Dimensional Stability w/Exposure to Heat	ISO 23999	Pass
Determination of Geometrical Characteristics	ISO 24337	Pass
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds Standard
Static Load Limit	ASTM F970	PASS >250 LBS
Flammability/Radiant Flux	ASTM E648	Class I
Smoke Density	ASTM E662	Pass
Impact Insulation Class IIC	ASTM E492*	
Sound Transmission Class STC	ASTM E90*	

*The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

Health & Environmental

Phthalate-Free





Warranty & Maintenance

10 Yr Light Commercial, 10 Yr Multi-Family, 30 Yr Residential

Accessories

Trims: T Mold, Reducer, End Cap, Stair Nose, Quarter Round <u>QNose</u> Stair Nosing

Layout Options:

