

RSPC 5.0 MM, 22 MIL



Risotto | MJRC0101



Paella | MJRC0102



Toasted | MJRC0103



Arancini | MJRC0104



Curry | MJRC0105



Porridge | MJRC0106



Basmati | MJRC0107

SPECIFICATIONS

Construction	RSPC, Rice Husk Stone Polymer Composite Core
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	7.25" Wide x 48" Long, 181 mm x 1120 mm
Overall Thickness	5.0 mm (includes 1 mm pad)
Wear Layer	22 mil
Finish Coat	Low Gloss, Polyurethane
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	23.79 sf/carton - 50 carton/pallet - 1189.5 sf/pallet
Installation	Angle / Drop & Tap
Warranty	10 Yr Light Commercial, 10 Yr Multi-Family, 30 Yr Residential

INSTALLATION FAST FACTS

- Transitions required for rooms larger than 50' W x 50' L
- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F
- Hydro Radiant Heat approved (≤ 85°F)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 55%
- Floor Flatness to 1/8" in 6'
- Floating floors must be allowed to expand and contract with no restrictions

Read Complete Instructions Before Installing



SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE

tasflooring.com

