

PALLADIUM



SPC 4.0 MM, 12 MIL



Chauny Marble | NFRCU0501



Eden Carrara | NFRCU0502

SPECIFICATIONS

Construction	SPC Rigid Core, Stone Polymer Composite
Dimensions	12" Wide x 24" Long, 300 mm x 600 mm
Overall Thickness	5.0 mm (includes 1 mm IXPE pad)
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Installation	Angle / Angle
Warranty	25 Yr Residential, 5 Yr Light Commercial, 5 Yr Multi-Family,
Packaging	22.066 sf/carton - 60 carton/pallet - 1324 sf/pallet

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Recommended Room Temp: 60°F-85°F after install
- Expansion Space: 1/4" gap
- Transition required for rooms larger than 50'W x 50'L
- Subfloors dry and flat (3/16" in 10')

Read Complete Instructions Before Installing



tasflooring.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE



Additional Specifications, Full Installation Instructions & Warranty Information Available Online

tasflooring.com | a division of T&A supply company, inc. Jan 2024