

Why LifeProtect?

With an impressive 80-hour water resistance, you can rest assured that your floors will withstand spills and splashes. LifeProtect's low swell core boasts a 4-5% swell rate, which remarkably retracts back to 1% within 72 hours.

LifeProtect's commitment to sustainability begins with sourcing of USA grown Oak and Maple trees for the HDF core. Furthermore, its locking system is milled with smaller tolerances, offering a superior lock for a strong lock and superior water protection.

LifeProtect's resin binder is derived from polyurethane, providing exceptional water resistance, lower VOC emissions, and excellent stability. This collection is also PVC-Free and has no added formaldehyde. LifeProtect is also Green Guard Gold certified, guaranteeing that our laminate meets strict standards for low chemical emissions, providing a safer and healthier environment for you and your loved ones.

With LifeProtect Laminate flooring, you can enjoy a beautiful, high-performance, water-resistant, and environmentally friendly flooring solution that will exceed your expectations.

DID YOU KNOW?



WEAR SURFACE

With an AC4 rated wear surface, LifeProtect delivers an incredibly durable, scratch and dent resistant floor.



MADE IN THE USA

LifeProtect flooring is domestically stocked and manufactured in the USA.



WATER **RESISTANT**

LifeProtect's 80-hour, ultra low swell core provides water resistant protection against spills and splashes.



INSTALLATION TYPES

Floating installation.

Specifications

Construction:~8~mm~Water~Resistant~Core~Laminate~+~2~mm~XPS~Attached~Pad

Dimensions: 8-1/32" Wide 47-5/8" Long

 $\label{eq:continuous} \textbf{Overall Thickness:} \ 10 \ \text{mm} \ (\text{includes} \ 2 \ \text{mm} \ \text{XPS} \ \text{Attached Pad})$

Edge Profile: 4-Sided Painted Bevel

Wear Surface: AC4 Rated Texture: Embossed

Installation: Angle/Horizontal Tap

Warranty: Lifetime Residential, 10 Yr Light Commercial, 10 Yr Multi-Family

Packaging: 18.6 sf/ctn, 68 ctn/plt, 1264.8 sf/plt 18.6 sf/ctn, 72 ctn/plt, 1339.2 sf/plt



A Division of

