

GRAND CANYON



20 OZ, 100% SOLUTION DYED POLYESTER

Construction	Solution Dyed Polyester Textured Loop Woven Polypropylene Secondary Backing
Roll Dimensions	12' Wide x 150' Average Roll Length
Weight	20 oz
Gauge	1/10"
Density oz/yd ³	6786 oz
TARR	3.0

Installation & Maintenance

Glue Down Adhesive: Power Hold 3000
Seam Sealer: Glue Down: Taylor 775, Stretch In: Traxx Fusion
Follow CRI Carpet Installation Guidelines

Test Method & Requirements

Pill Test		Passes
Flooring Radiant Panel	ASTM E648	Class I
Indoor Air Quality	GLP 9986	
Smoke Density	ASTM E662	Less Than 450
Static Test	AATCC-134	Less Than 3.5 kv
Lightfastness		Passes

Health & Environmental

CRI Green Label Plus # GLP9986

Warranty

Lifetime Commercial - Stain, Colorfast, Static
10 Year Wear

Installation Fast Facts

Follow CRI Carpet Installation Standards and Guidelines
Inspect new flooring prior to installation
Clean up spills immediately
Vacuum regularly and use walk-off mats at entrances
Use floor protection for furniture



Additional Info
Warranty
Installation & Maintenance

tasflooring.com

